



AdScape-HDMI & AdScape-DP 4K Expanders


AdScape 4K Expander



AdScape-HDMI and AdScape-DP are expansion boxes for the VuScape Video Wall Controllers, to expand a 4K output image to 4x 1080p displays. AdScape is ideal for large video walls and can be mounted behind the display wall to reduce cabling costs. Multiple boxes can be connected to a single 24x 4K output VuScape controller to expand the number of outputs to 96x 1080p displays.



Plug and play with default output arrangement of 2x2 set for the most common scenarios. Output arrangement can be set from the front panel to additional simple arrangements: 2x1, 1x2, 2x2, 3x1, 1x3, 4x1, 1x4 in both portrait and landscape. Manage multiple AdScape units over the network with the AdScape Configurator software to customize output arrangements in mixed resolutions and bezel management.



Features

Ultra-fast scaling process with latency at a fraction of a frame



HDCP supported

Flexible with customizable output arrangements and resolutions

Output rotation supported in 90 degree steps

👸 Bezel compensation and overlap

🌉 Embedded audio passthrough


Front panel button for easy set up


Powered by VuTrex[™] technology.





Example Diagram: Expanding a VuScape with 16x 4K outputs to 64x 1080p video wall displays





Example Scenarios

Expand a VS10 with 4x 4K60 outputs to 16x 1080p60 video wall displays



👸 Expand a VuScape with 24x 4K outputs to 96x 1080p video wall displays

AdScape Technical Speci ications

Model	AdScape-HDMI	AdScape-DP
Input	HDMI	DisplayPort 1.2
Max Input Resolutions	3840x2160 @60Hz, 3840x2160 @30Hz, 7680x1080 @60Hz, 7680x1080 @30Hz, 1920x4320 @60Hz, 1920x4320 @30Hz Contact VuWall for custom resolutions	
Input Color Space	RGB: 24 bits per pixels YUV: 4:4:4, 4:2:2 (8 bits per component)	
Outputs	4 x HDMI	
Max Output Resolutions	1920x1080 @60Hz, 1920x1080 @30Hz, 1920x1200 @60Hz, 1920x1200 @30Hz	
Output Color Space	RGB: 24 bits per pixels	
Output Rotation	0, 90, 180 & 270 degrees	
HDCP Support	Yes	
Audio Pass-Through to Select Outputs	AAC, PCM, Stereo, and Mono 44.1KHz and 48KHz 16-bit stereo	
Preconfigured Simple Arrangements	$2x1$, $1x2_{\underline{x}}2x2$, $3x1$, $1x3$, $4x1$, $1x4$ in both portrait and landscape	

Contact Information

CORPORATE HQ

VuWall Technology Inc. 181 Hymus Blvd., Suite 301 Montreal, Quebec H9R 5P4, Canada +1 514 505 4436

UNITED STATES HQ

VuWall USA Inc. 2662 Holcomb Bridge Road Suite 326 Roswell, GA, 30076 USA (844) 933 9255

EUROPEAN HQ

VuWall Technology Europe GmbH Birnenweg 15 72766 Reutlingen Germany +49 7121 766620



Control what you see. www.vuwall.com sales@vuwall.com